

CERTIFICATE OF ACCREDITATION

The ANSI National Accreditation Board

Hereby attests that

Kanawha Scales and Systems LLC

1387 Clarendon Ave S.W. Canton, OH 44710

Fulfills the requirements of

ISO/IEC 17025:2017

In the field of

CALIBRATION

This certificate is valid only when accompanied by a current scope of accreditation document. The current scope of accreditation can be verified at www.anab.org.

Jason Stine, Vice President

Expiry Date: 27 March 2025 Certificate Number: L1166.10-1









SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

Kanawha Scales and Systems LLC

1387 Clarendon Ave S.W. Canton, OH 44710 Candice Bryant 304-755-8321

CALIBRATION

Valid to: March 27, 2025 Certificate Number: L1166.10-1

Mass and Mass Related

Version 004 Issued: May 23, 2023

Parameter/Equipment	Range	Expanded Uncertainty of Measurement (+/-) ³	Reference Standard, Method, and/or Equipment
Class I, Unmarked and High Precision Lab Balances ¹	(0 to 500) mg (1 to 50) g (51 to 50 000) g	0.012 mg 0.000 3 % of Applied Load 0.000 5 % of Applied Load	ASTM E617 Class 1 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
Class II, Unmarked and High Precision Balances & Scales ¹	(0 to 500) mg (1 to 50) g (51 to 50 000) g	0.032 mg 0.000 7 % of Applied Load 0.001 7 % of Applied Load	ASTM E617 Class 2 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
Class III, Unmarked & Equivalent Industrial Scales 1,2	(0.02 to 500 000) lb (0.01 to 100 000) kg	0.013 % of Applied Load 0.013 % of Applied Load	NIST Class F and/or ASTM E617 Class 6 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
Class IIIL Vehicle and Hopper Scales ¹	(10 000 to 500 000) lb	0.031 % of Applied Load	NIST Class F and/or ASTM E617 Class 6 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the standard uncertainty of the measurement multiplied by a coverage factor of 2 (*k*=2), corresponding to a confidence level of approximately 95%.





Notes:

- 1. On-site calibration service is available for this parameter, since on-site conditions are typically more variable than those in the laboratory, larger measurement uncertainties are expected on-site than what is reported on the accredited scope.
- 2. Industrial Scales include but not limited to lab balances, bench and floor scales, tank and hopper scales and vehicle scales
- 3. The CMCs for balances and scales are highly dependent on the resolution of the unit under test. The CMCs presented here do not include the resolution of the unit under test. The resolution will be included in the reported uncertainty at the time of calibration.
- 4. Laboratory offers custom (specific scale) uncertainty budget when requested by client.
- 5. This scope is formatted as part of a single document including Certificate of Accreditation No. L1166.10-1

M

Jason Stine, Vice President

Version 004 Issued: May 23, 2023



