

# CERTIFICATE OF ACCREDITATION

## The ANSI National Accreditation Board

Hereby attests that

## Kanawha Scales and Systems LLC 100 Piper Lane Alabaster, AL 35007

Fulfills the requirements of

**ISO/IEC 17025:2017** 

In the field of

## **CALIBRATION**

This certificate is valid only when accompanied by a current scope of accreditation document. The current scope of accreditation can be verified at <a href="https://www.anab.org">www.anab.org</a>.

Jason Stine, Vice President

Expiry Date: 27 March 2027 Certificate Number: L1166.07-1







### SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

### Kanawha Scales and Systems LLC

100 Piper Lane Alabaster, AL 35007 Candice Bryant 304-755-8321

### **CALIBRATION**

Valid to: March 27, 2027 Certificate Number: L1166.07-1

#### Mass and Mass Related

Version 010 Issued: March 26, 2025

Mass and Mass Related			
Parameter/Equipment	Range	<b>Expanded Uncertainty of</b>	Reference Standard, Method,
Turumeter, Equipment	Tunge	Measurement (+/-) <sup>3</sup>	and/or Equipment
Parameter/Equipment	Range	Expanded Uncertainty of Measurement (+/-) <sup>3</sup>	Reference Standard,
			Method, and/or
	\ \	Wieasurement (+/-)	Equipment
Class I, Unmarked and High Precision Lab Balances <sup>1</sup>	(0 to 50) g	0.14 mg	ASTM E617 Class 1 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
	100 g	0.37 mg	
	200 g	0.24 mg	
	300 g	0.64 mg	
	500 g	0.97 mg	
	1 000 g	1.8 mg	
	2 000 g	3.5 mg	
	5 000 g	0.012 g	
	10 000 g	0.019 g	
	20 000 g	0.035 g	
	25 000 g	0.060 g	
	50 000 g	0.095 g	
Class II, Unmarked and High Precision Balances & Scales <sup>1</sup>	(0 to 200) g	0.000 37 % of Applied Load	ASTM E617 Class 2 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
	300 g	0.000 43 % of Applied Load	
	(301 to 2 000) g	0.000 36 % of Applied Load	
	(5 000 to 50 000) g	0.000 5 % of Applied Load	
Class III, Unmarked & Equivalent Industrial Scales <sup>1,2</sup>	(0.1 to 100 000) lb	0.013 % of Applied Load	NIST Class F and/or ASTM E617 Class 6 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
	(100 000 to 300 000) lb	0.003 % of Applied Load	
	(0.1 to 1.2) kg	0.024 % of Applied Load	
	(1.2 to 100 000) kg	0.01 % of Applied Load	

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the standard uncertainty of the measurement multiplied by a coverage factor of 2 (k=2), corresponding to a confidence level of approximately 95%.





#### Notes:

- 1. On-site calibration service is available for this parameter, since on-site conditions are typically more variable than those in the laboratory, larger measurement uncertainties are expected on-site than what is reported on the accredited scope.
- 2. Industrial Scales include but not limited to lab balances, bench scales, floor scales, crane/hanging scales, tank and hopper scales, forklift scales and vehicle scales.

  3. The CMCs for balances and scales are highly dependent on the resolution of the unit under test. The CMCs presented here do not include the resolution of the unit under test. The resolution will be included in the reported uncertainty at the time of calibration.
- 4. This scope is formatted as part of a single document including Certificate of Accreditation No. L1166.07-1

Jason Stine, Vice President



