

CERTIFICATE OF ACCREDITATION

The ANSI National Accreditation Board

Hereby attests that

Kanawha Scales and Systems LLC 5525 Chantry Drive Columbus, OH 43232

Fulfills the requirements of

ISO/IEC 17025:2017

In the field of

CALIBRATION

This certificate is valid only when accompanied by a current scope of accreditation document. The current scope of accreditation can be verified at www.anab.org.

Jason Stine, Vice President

Expiry Date: 27 March 2027 Certificate Number: L1166.06-1



ANSI National Accreditation Board



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

Kanawha Scales and Systems LLC

5525 Chantry Drive Columbus, OH 43232 Candice Bryant 304-755-8321

CALIBRATION

Valid to: March 27, 2027 Certificate Number: L1166.06-1

Mass and Mass Related

Version 010 Issued: March 26, 2025

Parameter/Equipment	Range	Expanded Uncertainty of	Reference Standard, Method,
		Measurement (+/-) ³	and/or Equipment
Class I, Unmarked and High Precision Lab Balances ¹	(0 to 50) g 100 g 200 g 300 g 500 g 1 000 g 2 000 g 10 000 g 20 000 g 25 000 g 50 000 g	0.14 mg 0.37 mg 0.24 mg 0.64 mg 0.97 mg 1.8 mg 3.5 mg 0.012 g 0.019 g 0.035 g 0.060 g 0.095 g	ASTM E617 Class 1 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
Class II, Unmarked and High Precision Balances & Scales ¹	(1 to 200) g 300 g (301 to 2 000) g (5 000 to 50 000) g	0.000 37 % of Applied Load 0.000 43 % of Applied Load 0.000 36 % of Applied Load 0.000 5 % of Applied Load	ASTM E617 Class 2 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System
Class III, Unmarked & Equivalent Industrial Scales ^{1,2}	(0.1 to 100 000 lb) (1 to 300 000) lb (0.1 to 1.2) kg (1.2 to 100 000) kg	0.013 % of Applied Load 0.003 % of Applied Load 0.024 % of Applied Load 0.01 % of Applied Load	NIST Class F and/or ASTM E617 Class 6 Weights and NIST Handbook 44 utilized for the calibration of the Weighing System





Parameter/Equipment	Range	Expanded Uncertainty of	Reference Standard, Method,
		Measurement (+/-) ³	and/or Equipment
Class IIIL Vehicle and Hopper Scales ¹	(1 to 100 000) lb	0.013% of Applied Load	NIST Class F and/or ASTM E617
	(100 000 to 300 000) lb	0.003% of Applied Load	Class 6 Weights and NIST
			Handbook 44 utilized for the
	(0.1 to 1.2) kg	0.024% of Applied Load	calibration of the Weighing
	(1.2 to 100 000) kg	0.01% of A <mark>ppli</mark> ed Load	System

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the coverage factor of 2 (*k*=2), corresponding to a confidence level of approximately 95%.

- 1. On-site calibration service is available for this parameter, since on-site conditions are typically more variable than those in the laboratory, larger measurement uncertainties are expected on-site than what is reported on the accredited scope.
- 2. Industrial Scales include but not limited to lab balances, bench scales, floor scales, crane/hanging scales, tank and hopper scales, forklift scales and vehicle scales.
- 3. The CMCs for balances and scales are highly dependent on the resolution of the unit under test. The CMCs presented here do not include the resolution of the unit under test. The resolution will be included in the reported uncertainty at the time of calibration.
- 4. This scope is formatted as part of a single document including Certificate of Accreditation No. L1166.06-1

Jason Stine, Vice President

Version 010 Issued: March 26, 2025



